



INDIVIDUAL SLATE AND TILE SOAKERS

20 YEAR GUARANTEE

The individual soakers range is compatible with a wide range of tiles and slates with both right and left hand options where required.



FEATURES AND BENEFITS

- All tile soakers available in both left and right hand options
- Thermally stable
- UV and acid rain resistant
- GRP can be used in water collection and reclamation systems; unlike lead which contaminates run-off water
- Unlike heavy metals, which come with an increased risk of theft, GRP offers no scrap value
- Dry fix products eliminate the mortar installation and maintenance issues

APPLICATION

A range of lead-free preformed soakers for roof abutment details covering interlocking flat tiles, single lap slate and plain tiles, and double lap plain tiles and slates.


They are supplied preformed to save time and effort on site, and are finished by the use of a lead or lead replacement flashing product.

MATERIAL

Polypropylene

PLEASE SEE
OVERLEAF
FOR
COMPATIBILITY

PRODUCT CODE AND DIMENSIONS

 GREY * 100% recycled grey PPC	Interlocking Tiles HD MDS H: 75mm W: 185mm L: 430mm	 BLACK ** up to 50% recycled PPC	Interlocking Slates HD RCS H: 105mm W: 155mm L: 280mm
 GREY * 100% recycled grey PPC	Interlocking Tiles HD RRS H: 75mm W: 180mm L: 430mm	 BLACK ** up to 50% recycled PPC	Plain Tiles HD PCS H: 75mm W: 100mm L: 170mm
 GREY * 100% recycled grey PPC	Interlocking Tiles HD RTS H: 75mm W: 175mm L: 410mm	 BLACK ** up to 50% recycled PPC	Slates HD SS500 H: 85mm W: 100mm L: 300mm
 GREY * 100% recycled grey PPC	Interlocking Tiles HD SRRS H: 75mm W: 180mm L: 430mm	 BLACK ** up to 50% recycled PPC	Slates HD SS600 H: 85mm W: 100mm L: 380mm
 BLACK ** up to 50% recycled PPC	Interlocking Plain Tiles HD DTS H: 105mm W: 145mm L: 240mm	* 100% recycled grey PPC ** up to 50% recycled PPC	

RELATED PRODUCTS

	Universal Abutment Cover Flashing A continuous GRP cover flashing in Anthracite, designed as an effective lead alternative for roof abutments. Code: HD UACF
	DaneFlash An environmentally friendly, lead-alternative flashing. Available in 3 colours of 5 metre roll lengths and in 4 widths. codes: DANEFLASH 140, 280, 370, 560mm
	Tile & Slate Vapour Permeable Roofing Underlays Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180

INDIVIDUAL SOAKER COMPATIBILITY

BMI (REDLAND)

Cambrian	RCS
Duo Plain	DTS
Landmark Slate 10	RTS
Mini Stonewold	MDS
Richmond	RRS
Richmond 10	RTS
Saxon 10	RTS
Stonewold Mkl	MDS

BREEDON

Elite	SRRS
Flat	MDS

DOUBLE LAP TILES AND SLATES

Plain Tiles (All)	PCS
Slates 500mm x 250mm	SS500
Slates 600mm x 300mm	SS600

FORTICRETE

Gemini	DTS
Minislate	DTS

F P McCANN

Thin Flat	RTS
-----------	------------

MANNOK (QUINN)

Devenish	RTS
Rathmore	RTS
Western Slate	MDS

MARLEY

Ashmore	DTS
Duo Modern	MDS
Edgemere	SRRS
Melbourn	RCS
Modern	MDS

RUSSELL

Bute	SRRS**
Galloway	RTS
Grampian	MDS
Highland	MDS
Lothian	RTS
Moray	RTS
Polden	RTS

WIENERBERGER (SANDTOFT)

Balmoral	SRRS
Britlock	RCS*
Calderdale Slate	MDS
Cassius	SRRS**
Danum TLE	MDS
Dual Calderdale	MDS
Rivius	SRRS**
TLE	RTS
20/20	SRRS**



♻️ * 100% recycled grey PPC
♻️ ** up to 50% recycled PPC

* Subject to minimum rafter pitch of 30° and minimum headlap of 95mm
** Longer than the tiles; the length maybe trimmed at the head if required

