



CLAY6+ DRY RIDGE AND HIP SYSTEM

15 YEAR GUARANTEE

CLAY6+ is a universal ventilated dry fix ridge and hip system that can be used with all the commonly available clay and baby ridge tiles. CLAY6+ can be fitted to all roof pitches* with no special tools required. The single unique universal jointing gasket adds flexibility and allows compatibility with the most commonly available ridge and hip tile profiles, including baby ridges.

FEATURES AND BENEFITS

- Unique flexible and trimmable patented gasket features weatherproof, continuous integrated water channels and self-sealing detail for the stainless steel fixing screws
- Broader corrugations of the roll membrane edge compliment a variety of ridge tile designs and different roof pitches
- Suitable for ridge and hip tile applications
- Wider butyl strip provides improved and secure adhesion
- Stainless steel batten straps included
- Dry fix products eliminate the mortar installation and maintenance issues

PACK CONTENTS

1 x 320mm x 6m Rollflex Ridge Roll, 20 x Uni-Ridge Gaskets*, 20 x Ridge Fixing Plates, 20 x 100mm Ridge Screws, 10 x Ridge Batten Straps

* Subject to being used in conjunction with ridge tiles suitable for that pitch



♻️ Fixing plates contain up to 30% recycled impact modified PA 6.6, Universal gaskets contain up to 30% recycled LDPE

PRODUCT CODE


HD CLAY6


TECHNICAL INFORMATION


- Provides compliance with BS 5250 and BS 5534
- Minimum 5,000mm² airflow area per linear metre installed (actual 11,700mm²)
- Suitable for warm and cold roof applications
- Complies with BS 8612
- **Patent Application No. GB2402727.8**
- **Registered design No. GB6349445**

COMPONENT	MATERIAL SPECIFICATION
Ridge Fixing Plate	High impact polyamide
Uni-Ridge Gasket	LDPE
Ridge Batten Strap	Stainless Steel
Ridge Screw	Stainless Steel
Rollflex Ridge Roll	Polypropylene fabric with corrugated aluminium edges

RELATED PRODUCTS

	Tile Clip For small interlocking tile cuts on hips and in valleys, code: HD DVC
--	---

	Hip Tile Support Trays (optional) 1.65m length, code HDL HT165 3m length, code: HDL HT300 (Subject to hip tile size compatibility)
--	--

	Vapour Permeable Roofing Underlays Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180
--	---